

Skyline Inverter - SLLI-900/SLLI-1500

Power Backup + Protection

Give Protection from Power impurities.

Save your work & equipment when Power goes.



- Microprocessor controlled
- Selectable charging current : 10A or 20A
- Auto restart on AC mains restore
- Overload and short circuit protection
- Generators & Computer-related devices compatible
- Cold start function

Model	SL-LI-900-Adora	SL-LI-1500-Adora
Capacity	900VA / 600W	1500VA / 1050W
Input	230VAC	
Voltage	180-260 VAC (For personal computer)	
Voltage Range	100-300 VAC (For other loads)	
Output	230VAC ± 10 %	
Voltage Regulation (Batt. mode)	8-20 ms max.	
Transfer Time	Simulated Sine Wave	
Wave Form		
Battery	12VDC	24 VDC
Battery Voltage	13.7VDC ± 2%	27.4 VDC ± 2%
Floating Charge Voltage	10A or 20A	
Maximum Charge Current	100Ah – 200Ah	
Recommended Battery Capacity		
Protection	Full Protection	Overload and short circuit protection
Indicators	Line Mode	Green lighting
	Battery Mode	Yellow flashing
	Fault	Red lighting
Alarm	Battery Mode	Sounding every 10 seconds
	Low Battery	Sounding every second
	Overload	Sounding every 0.5 second
	Battery Replacement	Sounding every 2 seconds
	Fault	Continuously sounding
Physical	Dimension D x W x H (mm)	289 x 290 x 127
	Net. Wt. (Kg.)	7.00 10.00
Environment	Humidity	0 to 90% Relative Humidity(Noncondensing)
	Operating Temperature	0° to 50°
	Storage Temperature	-15° to 70°

Specification subject to change without prior intimation

